



- For Hi-temp and Lo-temp foodservice uses
- Premium grade, fully certified silicone adhesive sealant outperforms cheap hardware store brands
- Waterproof adhesive bonds better than generic sealants; won't peel; reduces service call-backs for leaks
- Air-cures overnight; tack-free in 15 minutes
- Standard and high temperature formulas
- Meets Federal and NSF standards for foodservice use

Easy-to-Use

- Will not sag during vertical, horizontal or overhead application
- 10 oz. one-piece plastic tube (non-removable tip)
- 3 oz. tube is ideal for small jobs and tight spaces. Special order with MOQ requirements
- Fits standard caulk guns

Temperature Range

- Standard formula is serviceable from -80°F to 400°F (-62°C to 204°C)
- High temperature formula is heat resistant to 500°F (260°C)

Part No.	Tube Size	Color	Max. Temp. (°F)	Qty./Carton	Wgt./Carton
63700000001	10.1 oz (299 ml)	Clear	400	12	10 lb (5 kg)
63700000002	10.1 oz (299 ml)	White	400	12	10 lb (5 kg)
63700000003	10.1 oz (299 ml)	Aluminum	400	12	10 lb (5 kg)
63700000004	10.1 oz (299 ml)	Black	400	12	10 lb (5 kg)
63700000005	10.1 oz (299 ml)	Red (Hi-Temp)	500	12	10 lb (5 kg)
63700000006	10.1 oz (299 ml)	Almond	400	12	10 lb (5 kg)
63700000031	3 oz (89 ml)	Clear	400	36	9 lb (1.5 kg)
63700000032	3 oz (89 ml)	White	400	36	9 lb (1.5 kg)
63700000033	3 oz (89 ml)	Aluminum	400	36	9 lb (1.5 kg)
63700000035	3 oz (89 ml)	Red (Hi-Temp)	500	36	9 lb (1.5 kg)
63700000036	3 oz (89 ml)	Almond	400	36	9 lb (1.5 kg)

NSF listed STD 051 for Food Zone Use. All Foods. Authorized by USDA for use in Federally inspected meat and poultry plants. When cured and washed, sealant meets requirement of FDA regulation No. 21 CFR 177.2600. Meets the following: U.S. FED.TTS-00230C, TTS-001543A, ASTM C920-79 and Canadian CGSB-19-GP-9MA Type 1. UL Recognized, File No. E175317.

